

LO BUFFER-AMPLIFIER

A-2050



Features

- Frequency Range 20.0 to 50.0 GHz
- 0 to +5 dBm Typical Input Power
- +21 dBm Typical Saturated Output Power

Electrical Specifications - Specifications guaranteed from -30 to +70°C, measured in a 50-Ohm system.

Parameter	Frequency (GHz)	Min	Тур	Max
Input (dBm)	20.0-50.0		+5 to +10	
Saturated Output Power (dBm)	20.0-50.0	+15	+21	
Small Signal Gain (dB)	20.0-50.0		23	
Noise Figure (dB)	20.0-50.0		7	
Bias Requirements (mA) 1				
+5.0 Volts DC			400	500
-5.0 Volts DC			10	20

¹It is recommended that the negative bias be applied before or concurrent with the positive bias.

Model Number	Description	Package Style
A-2050	20.0 to 50.0 GHz Amplifier	<u>ESPV</u>

¹Connectorized test fixtures available for most carrier and surface mount packages. Contact factory.

Marki Microwave reserves the right to make changes to the product(s) or information contained herein without notice. Marki Microwave makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Marki Microwave assume any liability whatsoever arising out of the use of or application of any product.

215 Vineyard Court, Morgan Hill, CA 95037 | Ph: 408.778.4200 | Fax 408.778.4300 | info@markimicrowave.com




LO BUFFER-AMPLIFIER

A-2050

Page 2

Frequency 20.0 to 50.0 GHz


Typical Performance



DATA SHEET NOTES:

- 1. Maximum input power without damage is +18 dBm at +70°C.
- 2. Specifications are subject to change without notice. Contact Marki Microwave for the most recent specifications and data sheets.

Marki Microwave reserves the right to make changes to the product(s) or information contained herein without notice. Marki Microwave makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does Marki Microwave assume any liability whatsoever arising out of the use or application of any product.



215 Vineyard Court, Morgan Hill, CA 95037 | Ph: 408.778.4200 | Fax 408.778.4300 | info@markimicrowave.com

www.markimicrowave.com