TERMINATIONS

SMA

up to 18 GHz

1 Watt

MCE INMET

MODELS: 3016A, 3016AC

SPECIFICATIONS:

Electrical:

Frequency Range	DC - 18 GHz
Standard Freq. Values	3, 6 & 18 GHz
VSWR	See Table
Impedance	50 Ohms
Input Power	1 Watt Avg. @ +25°C Derated Linearly to 0 Watts @ +125°C
Peak Power	250 Watts Max. (5uSec Pulse, .05% Duty Cycle)
Temperature Coefficient	±250 ppm/°C
Operating Temp Range	-65°C to +125°C

Mechanical:

SMA Connectors Mates with MIL-STD-348	
Body	Gold Plated Stainless Steel
Coupling Nut	Passivated Stainless Steel
Conductors	Gold Plated Beryllium Copper
Bead Chain	Passivated Stainless Steel



CHAIN DETAIL
3016AC

Model Number: 3016A
SMA Male Connector
Frequency Range: DC - 18 GHz
VSWR:

DC - 4 GHz	1.05:1 Max.
4 - 8 GHz	1.10:1 Max.
8 - 12.4 GHz	1.15:1 Max.
12.4 - 18 GHz	1.20:1 Max.

Model Number: 3016A-067
SMA Male Connector
Frequency Range: DC - 6 GHz
VSWR:

DC - 4 GHz	1.05:1 Max.
4 - 6 GHz	1.10:1 Max.

Model Number: 3016A-137
SMA Male Connector
Frequency Range: DC - 3 GHz
VSWR: 1.30:1 Max.



HOW TO ORDER:

Model Number: 3016AX-YYY

Style
= No Chain
C = Chain Included

Frequency Range
= DC - 18 GHz
067 = DC - 6 GHz
137 = DC - 3 GHz

Ordering Examples:

Model Number: 3016AC
DC - 18 GHz; SMA Male; Chain Included

Model Number: 3016A-067
DC - 6 GHz; SMA Male; No Chain

Model Number: 3016A
DC - 18 GHz; SMA Male: No Chain

Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.

3016A; REV A

300 DINO DRIVE • ANN ARBOR, MI 48103-9457 • U.S.A. • TELEPHONE 888-244-6638 OR 734-426-5553 • FAX 734-426-5557
WEBSITE: www.inmetcorp.com • E-Mail: sales@inmetcorp.com